



Versilic® SPX-50 Inventoried Sizes

Saint-Gobain Part Number	I.D.		O.D.		Wall Thickness		Length		Minimum Bend Radius		Maximum Working Pressure	
	In.	mm	In.	mm	In.	mm	Ft.	m	In.	mm	psi at 73°F	psi at 320°F
	ABX00001	1/32	0.8	3/32	2.4	1/32	0.8	50	15.25	1/8	3.2	22
ABX00002	1/16	1.6	1/8	3.2	1/32	0.8	50	15.25	1/4	6.4	14	13
ABX00003	1/16	1.6	3/16	4.8	1/16	1.6	50	15.25	1/4	6.4	22	21
ABX00004	3/32	2.4	5/32	4	1/32	0.8	50	15.25	1/4	6.4	11	10
ABX00005	3/32	2.4	7/32	5.6	1/16	1.6	50	15.25	1/4	6.4	18	16
ABX00006	1/8	3.2	3/16	4.8	1/32	0.8	50	15.25	3/8	9.6	9	8
ABX00007	1/8	3.2	1/4	6.4	1/16	1.6	50	15.25	1/2	12.8	14	13
ABX00009	5/32	4	7/32	5.6	1/32	0.8	50	15.25	3/4	19.2	7	6
ABX00011	3/16	4.8	1/4	6.4	1/32	0.8	50	15.25	1	25.6	7	6
ABX00012	3/16	4.8	5/16	8	1/16	1.6	50	15.25	1/2	12.8	11	10
ABX00013	3/16	4.8	3/8	9.6	3/32	2.4	50	15.25	3/8	9.6	14	13
ABX00014	3/16	4.8	7/16	11.2	1/8	3.2	50	15.25	3/8	9.6	18	16
ABX00016	1/4	6.4	5/16	8	1/32	0.8	50	15.25	1-1/2	38.4	5	4
ABX00017	1/4	6.4	3/8	9.6	1/16	1.6	50	15.25	3/4	19.2	9	8
ABX00018	1/4	6.4	7/16	11.2	3/32	2.4	50	15.25	5/8	16	12	11
ABX00019	1/4	6.4	1/2	12.8	1/8	3.2	50	15.25	5/8	16	14	13
ABX00022	5/16	8	7/16	11.2	1/16	1.6	50	15.25	1-1/4	32	7	6
ABX00023	5/16	8	1/2	12.8	3/32	2.4	50	15.25	5/8	16	10	9
ABX00024	5/16	8	9/16	14.4	1/8	3.2	50	15.25	3/4	19.2	7	6
ABX00027	3/8	9.6	1/2	12.8	1/16	1.6	50	15.25	1-1/2	38.4	9	8
ABX00028	3/8	9.6	9/16	14.4	3/32	2.4	50	15.25	1	25.6	11	10
ABX00029	3/8	9.6	5/8	16	1/8	3.2	50	15.25	1	25.6	6	5
ABX00033	7/16	11.2	5/8	16	3/32	2.4	50	15.25	1-3/4	44.8	8	7
ABX00036	1/2	12.8	5/8	16	1/16	1.6	50	15.25	3	76.8	5	4
ABX00037	1/2	12.8	11/16	17.6	3/32	2.4	50	15.25	1-3/4	44.8	7	6
ABX00038	1/2	12.8	3/4	19.2	1/8	3.2	50	15.25	1-1/2	38.4	9	8
ABX00045	5/8	16	13/16	20.8	3/32	2.4	50	15.25	3	76.8	6	5
ABX00046	5/8	16	7/8	22.4	1/8	3.2	50	15.25	2-1/2	64	7	6
ABX00053	3/4	19.2	1	25.6	1/8	3.2	50	15.25	2-1/2	64	7	6
ABX42062	1	25.6	1-1/4	32	1/8	3.2	25	7.62	5	128	5	4
ABX42069	1-1/4	32	1-1/2	38.4	1/8	3.2	25	7.62	6	153.6	5	4
ABX42074	1-1/2	38.4	2	51.2	1/4	6.4	25	7.62	7	179.2	6	5

Working pressures are calculated at a 1:5 ratio relative to burst pressure using ASTM D1599.